

FORTRA

Clearswift Secure Email Gateway
Version 6.1.0

Installation Guide
(on Amazon Web Services)

Copyright Terms and Conditions

Copyright © Fortra, LLC and its group of companies. All trademarks and registered trademarks are the property of their respective owners.

The content in this document is protected by the Copyright Laws of the United States of America and other countries worldwide. The unauthorized use and/or duplication of this material without express and written permission from Fortra is strictly prohibited. Excerpts and links may be used, provided that full and clear credit is given to Fortra with appropriate and specific direction to the original content.

202506250245

Contents

Copyright Terms and Conditions	ii
Contents	iii
1. About this guide	4
Who is this guide for?	4
Alternative installation types, upgrade and migration	4
Identified issue in this release	4
2. Before installing	5
3. Subscribe to the Secure Email Gateway AMI	6
Subscribe to the AMI from AWS Marketplace	6
4. Launch the Secure Email Gateway instance	7
Initiate the launch instance wizard from the Amazon EC2 console	7
Configure the Launch an instance page	7
Name and tags	7
Application and OS Images (Amazon Machine Image)	7
Instance type	7
Key pair (login)	8
Network settings	8
Configure storage	9
Advanced details	9
Launch your instance	10
5. Peering within the Gateways	11
6. After you launch	12
Post-launch actions	12
Configure access to Red Hat Cockpit	12
FIPS mode	12
Complete the Initial Setup Wizard	13
Removing the AWS restriction on port 25	13
Appendix: FIPS mode	14
Enable FIPS mode	14
Contact Fortra	15
Fortra Support Portal	15

1. About this guide

This guide provides information for administrators installing Clearswift Secure Email Gateway on Amazon Web Services (AWS), using Amazon Machine Images (AMI). It covers the requirements and procedures necessary for a full installation.

Who is this guide for?

This guide is intended for use by:

- New and existing customers installing Secure Email Gateway version 6.1.0 on AWS.

Alternative installation types, upgrade and migration

This guide focuses on the installation of a new instance of Secure Email Gateway on AWS.

If you require information on the following, refer to the [Installation Guide](#).

- Alternative installation types: see the "**Before installing**" chapter.
- Upgrading from version 6.x to 6.1.0: see the "**Upgrade**" chapter.
- Migrating from version 5.7.0 to 6.1.0: see the "**Migrate**" chapter.



You can access all installation guides from the [Online Help](#).

Identified issue in this release

You might encounter an error, stating “Applying updates failed”, when updating via **Cockpit > Software updates**. This is due to an issue with the Red Hat Cockpit component.

- To resolve the error, run `dnf update` from the command line. Future updates via Cockpit should be unaffected.
- For more information, see [this knowledge article](#) in the Fortra Support Portal.

2. Before installing

We recommend being familiar with Amazon Web Services (AWS) and Amazon Machine Images (AMI) before you deploy Secure Email Gateway.

In this guide, we use:

- [AWS Marketplace](#) to subscribe to the AMI
- [Amazon Elastic Compute Cloud \(Amazon EC2\)](#), and the [Amazon EC2 console](#) to launch the instance



You must have an AWS account to complete all the steps described in this guide.

3. Subscribe to the Secure Email Gateway AMI

Subscribe to the AMI from AWS Marketplace

1. Sign in to [AWS Marketplace](#).
2. Locate the Secure Email Gateway product page.

You can either:

- type *Clearswift* in the search field
- from the **Categories** menu, select **Infrastructure Software > Security**. Refine the search results further by selecting *Fortra* from the **Publisher** section



AWS offers AMIs on a subscription basis. Secure Email Gateway uses a BYOL (Bring Your Own License) model.

3. Select the product.
4. In the product page, check the information and click **View purchase options**.
5. In the **Subscribe to this software** page, check the information and click **Continue to Configuration**.
6. In the **Configure this software** page, select the following:
 - **Fulfillment option**: 64-bit (x86) Amazon Machine Image (AMI)
 - **Software Version**: 6.1.0
 - **Region**: an appropriate regional data center for your organization



AWS Regions may vary according to proximity and cost, and should be selected carefully.

7. In the **Configure this software** page, click **Continue to Launch**.
8. In the **Launch this software** page, select the **Launch through EC2** from the **Choose Action** drop-down menu and click **Launch**.
9. You are redirected to the Amazon EC2 console.

4. Launch the Secure Email Gateway instance



AWS customers are required to perform all the necessary security configuration and management of their EC2 machines. This includes OS patching and AWS firewall configuration. For further information, see <https://aws.amazon.com/compliance/shared-responsibility-model/>.

Initiate the launch instance wizard from the Amazon EC2 console

By following the previous steps, you should automatically be redirected from AWS Marketplace to the [Amazon EC2 console](#).

Alternatively, you can access the Amazon EC2 console directly, click **Launch instance** in the dashboard, and configure your instance in the **Launch an instance** page.

Configure the Launch an instance page

Name and tags

You can tag the name of your instance.

1. In the **Name** field, enter a name for the instance.
2. Click **Add additional tags**.
3. Enter a corresponding **Key** and a **Value**, then click **Add new tag**.

Application and OS Images (Amazon Machine Image)

Specify an OS image (AMI) you are launching. This should be the AMI you have subscribed to.

Instance type

From the drop-down menu, select an instance type. There are a number of available options for building your machine.

Instance	vCPU	CPU Credits/hour	Mem (GiB)	Storage	Network Performance (GB/s)
t3.xlarge	4	96	16	EBS only	up to 5

Instance	vCPU	CPU Credits/hour	Mem (GiB)	Storage	Network Performance (GB/s)
t3.2xlarge	8	192	32	EBS only	up to 5
t3a.xlarge	4	96	16	EBS only	up to 5
t3a.2xlarge	8	192	32	EBS only	up to 5



Use an **xlarge** or larger instance for production workloads.

Key pair (login)

Select or create a key pair to ensure secure connection to your AMI.

Network settings

1. Click **Edit** in the **Network settings** panel.
2. From the **VPC** drop-down menu, select a VPC your instance belongs to.
3. From the **Subnet** drop-down menu, select an existing subnet from your VPC that matches your requirements.



For further information on Amazon Virtual Private Cloud, see <https://aws.amazon.com/vpc/> and its documentation.

4. From the **Auto-assign public IP** drop-down menu, select **Disable**.
5. In the **Firewall (security groups)** and **Inbound Security Group Rules** sections, you can select a security group to control traffic for your instance.

Use the following as a reference:

- **Type** - SSH, **Port range** - 22, **Source type** - restrict access to your valid IP addresses
- **Type** - SMTP, **Port range** - 25, **Source type** - anywhere
- **Type** - HTTPS, **Port range** - 443, **Source type** - restrict access to your valid IP addresses
- **Type** - TCP/UDP, **Port range** - 9090, **Source type** - restrict access to the Red Hat Cockpit UI



When configuring security group **Source type**, make sure you set rules to allow access from known IP addresses only. SMTP should be left unrestricted.

6. Click **Advanced network configuration**, and expand the section. **Advanced network configuration** is available only when you select the subnet.
7. For the **Network interface 1**, enter an IP address in the **Primary IP** field, or leave the field empty for an auto-assigned IP address.
8. If you are deploying PMM, you need to add a second NIC. Click **Add network interface** and configure the parameters.



[PMM](#) (Personal Message Management) is a component of Secure Email Gateway that enables your end-users to personally manage their held messages.

Configure storage

Configure your device storage. The **Configure storage** panel has two viewing modes; **Simple** and **Advanced**.

With the **Simple** view, you can specify the size and type of the volume. To display all parameters, click **Advanced** and switch the view.



Use the default devices provided with the AMI. These have been specifically partitioned for the deployment of Secure Email Gateway.

You can increase the **Size (GiB)** but you should not change the **Device name** or **Snapshot**.

Advanced details

Configure any additional parameters you require.



If you are launching multiple instances of Secure Email Gateway, and would like to peer them, you have to configure the following



before you launch the instances:

- **Number of instances** in the **Summary** panel
- **User data** in the **Advanced details** panel

See the [Peering within the Gateways](#) chapter of this guide for more information.

Launch your instance

Review your configuration in the **Summary** panel, and click **Launch instance**.


The user interface takes a few minutes to start.

5. Peering within the Gateways

You can deploy additional Secure Email Gateway instances to provide resilience and scalability. By peering your Gateways, you can manage them all from a single point.

On the **Launch an instance** page:

1. In the **Summary** panel, select a desired value for the **Number of instances** field.
2. Copy the following script, and paste it into the **User data** field in the **Advanced details** panel.

(Click  to open a page from where you can copy the commands and scripts.)



```
#!/bin/bash
```

```
NEWUUID=`uuidgen`
```

```
echo "machine.uuid=$NEWUUID" > /opt/cs-gateway/cfg/system-id.-  
properties
```

```
xmlstarlet ed -L -u "/System/@uuid" -v "$NEWUUID" /var/cs-gate-  
way/uicfg/system.xml
```

```
xmlstarlet ed -L -u "/System/PeerAppliances/Peer/@uuid" -v  
"$NEWUUID" /var/cs-gateway/uicfg/system.xml
```

6. After you launch

After the launch, you may need to perform some actions to set up your Secure Email Gateway, and then complete the Initial Setup Wizard.



For information on installation from this point onwards, please also refer to the "Configure Secure Email Gateway" chapter in the [Installation Guide](#).

Post-launch actions

We recommend the following after launching the instance, but before configuring the Secure Email Gateway's Initial Setup Wizard.

Configure access to Red Hat Cockpit

Before you access the Secure Email Gateway's web user interface, you must configure your Gateway's Linux user to access Red Hat Cockpit.

1. Access the SSH key pair.
2. Log in to the virtual machine using SSH, for example:

```
ssh -i keyPair.pem ec2-user@<ip-address>
```

3. Create a password for the root user in order to access Cockpit, for example:

```
sudo -i
```

```
passwd
```



To access the Cockpit administration user interface, open a supported web browser and enter the IP address of your Secure Email Gateway, on port 9090:

<https://<ip-address>:9090>

FIPS mode

If you wish to operate your Secure Email Gateway in FIPS mode, you need to configure it at this point. See the [Appendix](#) of this guide for more information.

If you are not using FIPS mode, you can skip this section.

Complete the Initial Setup Wizard

Once you have gone through the post-launch actions and have restarted Secure Email Gateway, run the Initial Setup Wizard.



To access the Secure Email Gateway's web user interface, open a supported web browser and enter the IP address of your Gateway:

<https://<ip-address>>

Removing the AWS restriction on port 25

AWS blocks outbound traffic on port 25 by default, so you will not be able to send emails unless this restriction is lifted. You will need to request AWS to lift the restriction.

For further information, see <https://aws.amazon.com/premiumsupport/knowledge-center/ec2-port-25-throttle/>.

Appendix: FIPS mode

Your Secure Email Gateway can operate in FIPS mode. This needs to be configured after you have launched an instance, but before completing the Secure Email Gateway's Initial Setup Wizard.

Enable FIPS mode

1. Access a command line terminal via SSH or Cockpit.
2. Execute the following:

```
fips-mode-setup --enable
```

3. Reboot, then return to the [Complete the Initial Setup Wizard](#) section of this guide and continue.



Once enabled, you cannot disable FIPS mode without reinstalling the Gateway.

For more information on FIPS mode, see the [Online Help](#).

Contact Fortra

For more information about the Fortra's Clearswift products and cybersecurity solutions, please visit our [website](#).

You can contact us for questions, and to receive technical bulletins, updates, program fixes and other information on your Secure Email Gateway via email or Internet.

Fortra Support Portal

[Fortra Support Portal](#) offers various helpful resources, such as product documentation and knowledge articles. You can also contact our Technical Support, using the Fortra Support Portal.

For support issues, please:

- Check this guide's table of contents and topics for information that addresses your concern.
- Check the Knowledge Base in the Fortra Support Portal for information that addresses your concern.
- Gather and organize as much information as possible about the problem, including job/error logs, screenshots or anything else to document the issue.